



Part Number	Length(L)mm
6232-9F9F-03CRTK	900 <sup>+60</sup> <sub>-0</sub>
6232-9F9F-06CRTK	1800 <sup>+100</sup> <sub>-0</sub>
6232-9F9F-10CRTK	3000 <sup>+100</sup> <sub>-0</sub>
6232-9F9F-15CRTK	4500 <sup>+100</sup> <sub>-0</sub>
6232-9F9F-33CRTK	10000 <sup>+150</sup> <sub>-0</sub>
6232-9F9F-50CRTK	15000 <sup>+150</sup> <sub>-0</sub>

### PIN ASSIGNMENT

P1		P2
1	BLACK	7
		8
2	BROWN	3
3	RED	2
4	ORANGE	6
5	YELLOW	5
6	GREEN	4
7	BLUE	1
8		
S	DRIAN	S

#### TEST CONDITION

1. OPEN/SHORT : 100%
2. INSULATION RESISTANCE: 10 Mohm min
3. CONTACT RESISTANCE: 1 ohm max
4. HI POT: DC300v/10ms

RoHS compliant product

⑥	Copper foil	Conductive COPPER FOIL W:27mm	-
⑤	Outer mold	PVC BEIGE 50P	BEIGE
④	Inner mold	PE	-
③	Screws	SRW E31.5 BEIGE #4-40	BEIGE
②	Plug	D-SUB-9P FEMALE CONTACT:G/F SHELL:NICKEL-PLATED	-
①	Cable	UL2464 28AWG × 7C+DW+AL/MY+JACKET OD4.3 BEIGE VW-1 300V	BEIGE
No	Material	Description	Color
Unit:mm	Approved	Checked	Desingner
		D SUB 9P FEMALE CABLE	Version: A