



### PIN ASSIGNMENT

Part Number	Length(L)mm
6232-9F9F-03TK	900 <sup>+60</sup> <sub>-0</sub>
6232-9F9F-06TK	1800 <sup>+100</sup> <sub>-0</sub>
6232-9F9F-10TK	3000 <sup>+100</sup> <sub>-0</sub>
6232-9F9F-15TK	4500 <sup>+100</sup> <sub>-0</sub>
6232-9F9F-33TK	10000 <sup>+150</sup> <sub>-0</sub>
6232-9F9F-50TK	15000 <sup>+150</sup> <sub>-0</sub>

P1		P2
1	BLACK	1
2	BROWN	2
3	RED	3
4	ORANGE	4
5	YELLOW	5
6	GREEN	6
7	BLUE	7
8	PURPLE	8
9	GRAY	9
S	DRIAN	S

**TEST CONDITION**

1. OPEN/SHORT : 100%
2. INSULATION RESISTANCE:10 Mohm min
3. CONTACT RESISTANCE: 1 ohm max
4. HI POT:DC300v/10ms

RoHS compliant product

⑥	Copper foil	Conductive COPPER FOIL W:27mm	-
⑤	Outer mold	PVC BEIGE 50P	BEIGE
④	Inner mold	PE	-
③	Screws	SRW E31.5 BEIGE #4-40	BEIGE
②	Plug	D-SUB-9P FEMALE CONTACT:G/F SHELL:NICKEL-PLATED	-
①	Cable	UL2464 28AWG × 9C+AI+D OD5.0 BEIGE VW-1 300V	BEIGE

No	Material	Description	Color
Unit:mm	Approved	Checked	Desingner
		<b>D SUB 9P FEMALE CABLE</b>	Version: <b>A</b>



**Part No:6232-9F9F-※※TK**