



PIN ASSIGNMENT

Part Number	Length(L)mm
6232-9M9F-03NUTK	900 ⁺⁵⁰ ₋₀
6232-9M9F-06NUTK	1800 ⁺⁷⁵ ₋₀
6232-9M9F-10NUTK	3000 ⁺⁷⁵ ₋₀
6232-9M9F-15NUTK	4500 ⁺⁷⁵ ₋₀
6232-9M9F-33NUTK	10000 ⁺¹⁵⁰ ₋₀
6232-9M9F-50NUTK	15000 ⁺¹⁵⁰ ₋₀

P1		P2
1	BLACK	1
2	BROWN	2
3	RED	3
4	ORANGE	4
5	YELLOW	5
6	GREEN	6
7	BLUE	7
8	PURPLE	8
9	GRAY	9
S	DRIAN	S

TEST CONDITION

1. OPEN/SHORT : 100%
2. INSULATION RESISTANCE:10 Mohm min
3. CONTACT RESISTANCE: 1 ohm max
4. HI POT:DC300v/10ms

RoHS2 compliant product

⑤	Cap	PVC BEIGE 50P	BEIGE
⑥	Copper foil	Conductive COPPER FOIL W:27mm	-
⑥	Screws	SRW E31.5 BEIGE #4-40	BEIGE
⑤	Outer mold	PVC BEIGE 50P	BEIGE
④	Inner mold	PE	-
③	Plug	D-SUB-9P FEMALE CONTACT:G/F SHELL:NICKEL-PLATED	-
②	Plug	D-SUB-9P/M CONTACT:G/F PBT:BK SHELL:NICKEL-PLATED #4-40	-
①	Cable	UL2464 9C×28AWG+AL+D OD5.0 BEIGE VW-1 300V	BEIGE

No	Material	Description	Color
----	----------	-------------	-------

Unit:mm	Approved	Checked	Desingner	D SUB 9P MALE 9P FEMALE CABLE	 https://cabledirect.jp	Version: A
---------	----------	---------	-----------	-------------------------------	--	------------

Part No:6232-9M9F-※※NUTK