



### PIN ASSIGNMENT

Part Number	Length(L)mm
6232-IC-9F9F-03TK	900 <sup>+60</sup> <sub>-0</sub>
6232-IC-9F9F-06TK	1800 <sup>+100</sup> <sub>-0</sub>
6232-IC-9F9F-10TK	3000 <sup>+100</sup> <sub>-0</sub>
6232-IC-9F9F-15TK	4500 <sup>+100</sup> <sub>-0</sub>
6232-IC-9F9F-33TK	10000 <sup>+150</sup> <sub>-0</sub>
6232-IC-9F9F-50TK	15000 <sup>+150</sup> <sub>-0</sub>

P1		P2
2	BLACK	3
3	BROWN	2
4	RED	6
5	ORANGE	5
6	YELLOW	4
7	GREEN	8
8	BLUE	7
S	DRIAN	S

#### TEST CONDITION

1. OPEN/SHORT : 100%
2. INSULATION RESISTANCE: 10 Mohm min
3. CONTACT RESISTANCE: 1 ohm max
4. HI POT: DC300v/10ms

RoHS compliant product

⑥	Copper foil	Conductive COPPER FOIL W:27mm	-
⑤	Outer mold	PVC BEIGE 50P	BEIGE
④	Inner mold	PE	-
③	Screws	SRW E31.5 BLACK #4-40	BLACK
②	Plug	D-SUB-9P FEMALE CONTACT:G/F SHELL:NICKEL-PLATED	-
①	Cable	UL2464 28AWG × 7C+DW+AL/MY+JACKET OD4.3 BEIGE VW-1 300V	BEIGE
No	Material	Description	Color
Unit:mm	Approved	Checked	Desingner
		D SUB 9P FEMALE CABLE	Version: A
			

Part No:6232-IC-9F9F-※※TK